

I-TECH Clearview Subsea Bullseyes are incredibly light and easy to handle, unit weights are shown in the table below.

Prior to deployment Subsea Bullseyes should be protected from sunlight, extreme temperatures, exposure to chemicals and impacts – to give your Bullseye maximum protection use the I-TECH Clearview EPC.

BULLSEYE SIZE	Ø407 mm 2° > 7° Bullseye	Ø350 mm 10° > 15° Bullseye	Ø350 mm 2° > 7° Bullseye	Ø300 mm 2° > 7° Bullseye	Ø250 mm 2° > 7° Bullseye	Ø150 mm 2° > 5° Bullseye	Ø100 mm 7° Bullseye
Bullseye only weight	10.7 kg	8.6 kg	8.0 kg	6 kg	4 kg	1.2 kg	0.5 kg
Bullseye + Top Mount Weight	14.1 kg	12.0 kg	11.3 kg	7.9 kg	5.9 kg	1.9 kg	1.2 kg
Bullseye + Side Mount Weight	20 kg	17.9 kg	17.3 kg	11.2 kg	9.2 kg	3.2 kg	2.5 kg
Bullseye + Portable Mount Weight	15.2 kg	13.1 kg	12.5 kg	8.8 kg	6.8 kg	TBC	TBC

BESPOKE BULLSEYES CAN BE MADE TO YOUR SPECIFICATION - PLEASE CONTACT OUR DESIGN TEAM WITH YOUR REQUIREMENTS.

CLEARVIEW™ MOUNTING SYSTEMS ARE AVAILABLE TO ENSURE INSTALLATION AND CALIBRATION OF YOUR BULLSEYE IS QUICK AND EASY - MORE INFORMATION IS AVAILABLE AT WWW.SUBSEABULLSEYE.COM AND FURTHER DETAILS CAN BE SUPPLIED ON REQUEST.